PHILIPS

Philips 3000 series 34B2U3600C/00 computer monitor 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD LCD Black

Brand : Philips **Product family:** 3000 series **Product code:** 34B2U3600C/00

Product name :
34B2U3600C/00

- 3000 series
- 34" (86.36 cm)
- 3440 x 1440 (WQHD)

Curved Business monitor 34B2U3600C WQHD monitor with USB-C

Philips 3000 series 34B2U3600C/00 computer monitor 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD LCD Black:

This monitor is all about quality. With its WQHD resolution, Smart KVM switch, and USB-C to RJ45 connectivity, it is the ideal option for switching between sources and connecting to the internet without compromising on picture quality.
Philips 3000 series 34B2U3600C/00. Display diagonal: 86.4 cm (34"), Display resolution: 3440 x 1440 pixels, HD type: Wide Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display	
Display diagonal *	86.4 cm (34")
Display resolution *	3440 x 1440 pixels
HD type *	Wide Quad HD
Native aspect ratio *	21:9
Display technology *	LCD
Panel type *	VA
LED backlight	✔
Backlight type	W-LED
Touchscreen *	✘
Display brightness (typical)	300 cd/m²
Response time *	4 ms
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	✔
Screen shape *	Curved
Screen curvature rating	1500R
Supported graphics resolutions	3440 x 1440
Contrast ratio (typical) *	3500:1
Contrast ratio (dynamic)	50000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	120 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
Pixel pitch	0.23175 x 0.23175 mm
Pixel density	110 ppi
Vertical scan range	48 - 100 Hz
Viewable size, horizontal	79.7 cm
Viewable size, vertical	33.4 cm

Ports & interfaces	
HDCP version	2.2
Network	
Ethernet LAN	✔
Ergonomics	
VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Adjustable height (max)	18 cm
Swivelling	✔
Swivel angle range	-180 - 180°
Tilt adjustment	✔
Tilt angle range	-5 - 30°
Picture-in-Picture	✔
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
LED indicators	✔
Power	
Energy efficiency class (SDR) *	D
Energy consumption (SDR) per 1000 hours *	20 kWh

Display	
Digital horizontal frequency	30 - 190 kHz
Digital vertical frequency	48 - 120 Hz
Display diagonal (metric)	86.36 cm
DDC/CI	✔
Haze rate	25%
Surface hardness	3H
Colour depth	10 bit
Colour gamut standard	sRGB, NTSC
sRGB coverage (typical)	120%
NTSC coverage (typical)	104%
Display sRGB	✔
Display panel size	34 inch / 86.36 cm

Performance	
VESA Adaptive Sync support	✔
Component video sync	Separate Sync, Sync-on-green (SOG)
Flicker-free technology	✔
Low Blue Light technology	✔
Windows operating systems supported	Windows 10, Windows 11
Mac operating systems supported	✔

Multimedia	
Number of speakers	2
RMS rated power	10 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design	
Market positioning *	Business
Product colour *	Black
Front bezel colour	Black
Feet colour	Black

Ports & interfaces	
Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	90 W
HDMI *	✔
HDMI ports quantity	1
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Audio output	✔
Built-in KVM switch	✔
HDCP	✔

Power	
Power consumption (typical) *	28.19 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0 W
Power consumption (PowerSave)	20.2 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m

Weight & dimensions	
Width (with stand)	807 mm
Depth (with stand)	287 mm
Height (with stand)	602 mm
Weight (with stand)	10.4 kg
Width (without stand)	807 mm
Depth (without stand)	107 mm
Height (without stand)	369 mm
Weight (without stand)	7.82 kg

Packaging data	
Package width	930 mm
Package depth	188 mm
Package height	525 mm
Package weight	15.3 kg

Packaging content	
Stand included	✔
Cables included	DisplayPort, HDMI, Power, USB Type-C to USB Type-C
Manual	✔
Bundled software	SmartControl

Sustainability	
Sustainability certificates	ENERGY STAR
Doesn't contain	Mercury, PVC/BFR

Other features	
HBR3 support	✔
Compatible operating systems	DDC/CI, Mac OS, sRGB, Windows 11 / 10
On/off switch	✔
USB Power Delivery revision	3.0
Picture-by-Picture (PbP)	✔
Exterior finish type	Textured
Monitor sync input signal	Separate Sync, Sync on Green
User controls	SmartImage, Input, User, Menu, Power On/Off
Picture enhancement	SmartImage
MultiView	2x devices, PIP/PBP mode
Regulatory Approvals	CB; CE Mark; EPA; TUV/GS; TUV Ergo; TCO Certified; TCO Certified Edge; EAC; EAC ROHS; MEPS; CEL; CCC; CECP; UKCA; EMF; FCC; ICES-003; eyesafe® CERTIFIED 2.0; TÜV Rheinland Low Blue Light (Hardware Solution)
SmartImage	✔
SoftBlue	✔

Other features	
EasyRead mode	✔
Compliance certificates	RoHS
Ethernet LAN (RJ-45) ports	1
Recycling data	
Packaging recyclability rate	100%
Product post-consumer recycled plastic	85%
Logistics data	
Export Control Classification Number (ECCN)	EAR99

8721038002409

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 29-OCT-2026. Prints or copies of Information are only valid on the printed Publication date