PHILIPS

Philips 6000 series 45B1U6900C/00 computer monitor 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD LED Black

Brand : Philips **Product family:** 6000 series **Product code:** 45B1U6900C/00

Product name :
45B1U6900C/00



Curved Business Monitor 45B1U6900C 32:9 SuperWide curved monitor with USB-C

Philips 6000 series 45B1U6900C/00 computer monitor 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD LED Black:

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth, high-resolution video, transfer data and charge your laptop. The headphone holder brings cable management to the next level.
Philips 6000 series 45B1U6900C/00. Display diagonal: 113 cm (44.5"), Display resolution: 5120 x 1440 pixels, HD type: UltraWide Dual Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display	
Display diagonal *	113 cm (44.5")
Display resolution *	5120 x 1440 pixels
HD type *	UltraWide Dual Quad HD
Native aspect ratio *	32:9
Display technology *	LED
Panel type *	VA
LED backlight	✔
Backlight type	W-LED
Touchscreen *	✘
Display brightness (typical)	450 cd/m²
Response time *	4 ms
Anti-glare screen	✔
Screen shape *	Curved
Screen curvature rating	1500R
Contrast ratio (typical) *	3000:1
Contrast ratio (dynamic)	80000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.2124 x 0.2124 mm
Pixel density	120 ppi
Horizontal scan range	30 - 114 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	108.7 cm
Viewable size, vertical	30.6 cm
Display diagonal (metric)	113 cm

Network	
Ethernet LAN	✔

Ergonomics	
VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Adjustable height (max)	15 cm
Swivelling	✔
Swivel angle range	-45 - 45°
Tilt adjustment	✔
Tilt angle range	-5 - 15°
Picture-in-Picture	✔
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Portuguese, Czech, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	✔
LED indicators	Operation, Stand-by

Power	
Energy efficiency class (SDR) *	G
Power consumption (typical) *	46.3 W
Power consumption (standby) *	0.3 W

Display	
High Dynamic Range (HDR) supported	✔
High Dynamic Range (HDR) technology	DisplayHDR 400
DDC/CI	✔
Haze rate	25%
Surface hardness	2H
Colour depth	8 bit
Colour gamut standard	sRGB, NTSC
Colour gamut	107%
sRGB coverage (typical)	123%
NTSC coverage (typical)	107%
Display sRGB	✔
Display panel size	44.5 inch/113 cm

Performance	
VESA Adaptive Sync support	✔
Component video sync	Separate Sync
Flicker-free technology	✔

Multimedia	
Number of speakers	2
RMS rated power	10 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design	
Market positioning *	Business
Product colour *	Black
Frameless design	✔
Front bezel colour	Black
Feet colour	Black

Ports & interfaces	
Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	100 W
HDMI *	✔
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Audio output	✔
Built-in KVM switch	✔
HDCP	✔
HDCP version	2.2
AC (power) in	✔

Power	
Power consumption (off)	0 W
Power consumption (PowerSave)	36.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m

Weight & dimensions	
Width (with stand)	1085 mm
Depth (with stand)	238 mm
Height (with stand)	515 mm
Weight (with stand)	12.8 kg
Width (without stand)	1085 mm
Depth (without stand)	158 mm
Height (without stand)	337 mm
Weight (without stand)	9.75 kg

Packaging data	
Package width	1180 mm
Package depth	535 mm
Package height	235 mm
Package weight	17.1 kg

Packaging content	
Stand included	✔
Cables included	HDMI, DisplayPort, USB Type-C, AC
Manual	✔
Bundled software	SmartControl

Sustainability	
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Mercury, PVC/BFR

Other features	
HBR3 support	✔
Compatible operating systems	Mac OS X; Windows 11/10/8.1/8
Picture-by-Picture (PbP)	✔
Exterior finish type	Textured
Monitor sync input signal	Separate Sync
Light sensor	✔
EasyRead mode	✔
LowBlue mode	✔
Philips SmartUniformity	93 - 105%
Compliance certificates	RoHS
User controls	KVM; SmartImage; Input; User; Menu; Power On/Off
Picture enhancement	SmartImage
MultiView	PIP/PBP mode; 2 x devices
Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; eyesafe® CERTIFIED 2.0; cETLus; TÜV Rheinland Low Blue Light (Hardware Solution)
Delta E	2
Mean time between failures (MTBF)	70000 h
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN	✔

Recycling data	
Packaging recyclability rate	100%
Product post-consumer recycled plastic	85%

8712581797454

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 03-NOV-2026. Prints or copies of Information are only valid on the printed Publication date