

Cisco SFP-10G-LR Compatible SFP+ Transceiver Module - 10GBASE-LR

Product ID: SFP10GLRSTTA



The SFP10GLRST is a TAA compliant Cisco SFP-10G-LR compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco™ brand switches and routers. It delivers dependable 10 GbE connectivity over fiber cable, for 10GBASE-LR compliant networks, with a maximum distance of up to 10 km (6.2 mi).

Technical Specifications:

- **Wavelength:** 1310nm
- **Maximum Data Transfer Rate:** 10 Gbps
- **Type:** Single Mode Fiber
- **Connection Type:** LC Connector
- **Maximum Transfer Distance:** 10 km (6.2 mi)
- **MTBF:** 1,203,430 hours
- **Power Consumption:** Less than 1 Watt
- **Digital Diagnostics Monitoring (DDM):** Yes

This SFP+ fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.

**Certifikat, rapporter
och kompatibilitet**



Användning

- Replacing defective or damaged SFP+ modules in Cisco switches and routers
- Expand your network to remote segments

Funktioner

- 100% compatibility with Cisco SFP-10G-LR guaranteed
- StarTech.com SFP modules are backed by a lifetime warranty
- Meets or exceeds OEM specifications and Multi-Source Agreement (MSA) industry standards
- Low power consumption of less than 1 W
- Hot-swappable with fiber-optic modules

Hårdvara	Warranty	Lifetime
	Compatible Brand	Cisco
	Industristandarder	IEEE 802.3ae 10 Gbit/s
Prestanda	DDM	Ja
	Fiber-driftsläge	Full-duplex
	Fibertyp	Enkelläge
	Kompatibla nätverk	10 Gbps
	Maximal dataöverföringshastighet	10 Gbps
	Maximalt överföringsavstånd	10 km (6.2 mi)
	Medeltid mellan fel (MTBF)	1 203 430 timmar
Kontakt(er)	Våglängd	1310nm
	Lokala enhetskontakter	1 - Fiberoptisk LC duplex Hona
Särskilda anmärkningar/krav	Obs.	For use in 10 Gigabit fiber networking equipment and media converters
	System- och kabelkrav	MSA or Cisco compliant SFP port
Ström	Strömförbrukning	< 1 W
Miljö	Drifttemperatur	0°C to 70°C (32°F to 158°F)
	Förvaringstemperatur	-40°C to 85°C (-40°F to 185°F)
	Luftfuktighet	5~95% RH
Utseende	Färg	Silver
	Kabinettyp	Zinkpläterat hölje
	Produktbredd	0.5 in [13.3 mm]
	Produkthöjd	0.4 in [10 mm]
	Produktlängd	2.2 in [57 mm]
	Produktvikt	0.7 oz [19 g]
Förpackning	Fraktvikt (förpackning)	0.1 lb [0.1 kg]
Vad det är i lådan	Ingår i paketet	1 - SFP+ transceiver

Produkters utseende och specifikationer kan komma att ändras utan förvarning.