

ZW350

Compact high brightness laser projector









- Bright WXGA DuraCore laser projector 3500 lumens and IP6X certified
- Easy installation 1.3x zoom, 360-degree and portrait projection
- Ultimate control Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- DuraCore laser technology 30,000 hours maintenance-free laser light source



The ZW350 is a compact WXGA DuraCore IP6X laser projector. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation. Its small and lightweight footprint and 1.3x zoom combined with 360-degree and portrait projection make it easy to install.

This feature-packed projector has a built-in speaker and its laser technology delivers up to 30,000 hours of maintenance-free laser light source. For ultimate control, it comes with an RJ45 connection for monitoring and controlling a network across multiple rooms.

Specifications

Power consumption (min)

Power consumption (max)

Gross weight

Net weight

Weight and dimensions Dimensions (W x D x H) mm

Display/image DIPTM Display technology Resolution WXGA (1280x800) Brightness 3,500 lumens Contrast ratio 300,000:1 16:10 Native aspect ratio Aspect ratio - compatible 4:3.16:9 Keystone correction - vertical +/-40° Has vertical auto keystone Yes correction Displayable colours (millions) 1073.4 Horizontal scan rate 15.375 ~ 91.146 Khz 50 ~ 85 Hz (120Hz for 3D)Hz Vertical scan rate Uniformity 75% 0.76m ~ 7.65m (30.1" ~ 301") diagonal Screen size Lamp info Light source type Laser LASER life 30,000 hours Optical Throw ratio 1.18:1 ~ 1.54:1 Projection distance (m) 1m - 7.7m Zoom 1.3 Manual Zoom type Focal length (mm) 16.901 ~ 21.6076 Native offset Connectivity Connections Inputs 2 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x micro USB service General Noise level (typical) 30dB 32dB Noise level (max) PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D compatibility 3D Full 3D Security Security bar, Kensington Lock, Password protected interface IP rating IP6X OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 24/7 operation Yes 360° operation Yes Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Remote control Data remote with laser and mouse function Speaker count Watts per speaker 15W In the box AC power cord Remote control 2x AAA batteries Basic user manual UHDCast Pro Optional wireless models Networking LAN - control Yes Power Power supply 100V ~ 240V, 50-60Hz Power consumption (standby) <0.5W

138W

161W

6.2 kg

4 kg

337 x 265 x 122.5





