


ThinkServer RD350 Platform Specifications

Product Specifications Reference (PSREF)

Components	Specification			
Dimensions	1U rack. Height: 43 mm (1.7 in), width: 482 mm (19 in), depth: 781.5 mm (30.77 in)			
Weight	Minimum configuration: 13 kg (28.66 lb), maximum: 19.1 kg (42.11 lb)			
Processor	Up to two 105W Intel Xeon E5-2600 v4 or E5-2600 v3 family processors.			
	E5-2660 v4	14C/2GHz/35MB/105W/DDR4-2400		
	E5-2650 v4	12C/2.2GHz/30MB/105W/DDR4-2400		
	E5-2640 v4	10C/2.4GHz/25MB/90W/DDR4-2133		
	E5-2630 v4	10C/2.2GHz/20MB/85W/DDR4-2133		
	E5-2623 v4	4C/2.6GHz/10MB/85W/DDR4-2133		
	E5-2620 v4	8C/2.1GHz/20MB/85W/DDR4-2133		
	E5-2609 v4	8C/1.7GHz/20MB/85W/DDR4-1866		
	E5-2603 v4	6C/1.7GHz/15MB/85W/DDR4-1866		
	E5-2650L v4	14C/1.7GHz/35MB/65W/DDR4-2400		
	E5-2630L v4	10C/1.8GHz/25MB/55W/DDR4-2133		
	E5-2660 v3	10C/2.6GHz/25MB/105W/DDR4-2133		
	E5-2650 v3	10C/2.3GHz/25MB/105W/DDR4-2133		
	E5-2640 v3	8C/2.6GHz/20MB/90W/DDR4-1866		
	E5-2630 v3	8C/2.4GHz/20MB/85W/DDR4-1866		
	E5-2623 v3	4C/3GHz/10MB/105W/DDR4-1866		
	E5-2620 v3	6C/2.4GHz/15MB/85W/DDR4-1866		
	E5-2609 v3	6C/1.9GHz/15MB/85W/DDR4-1600		
	E5-2603 v3	6C/1.6GHz/15MB/85W/DDR4-1600		
E5-2650L v3	12C/1.8GHz/30MB/65W/DDR4-2133			
E5-2630L v3	8C/1.8GHz/20MB/55W/DDR4-1866			
Chipset	Intel C610 Series Chipset			
Memory DIMMs	16 DIMM sockets. 4 channels per processor, 2 DIMMs per channel. RDIMM or LRDIMM (cannot be intermixed), DDR4-2133 or DDR4-2400			
Memory capacity	512GB (RDIMM, 32GB x 16)/1024GB (LRDIMM, 64GB x 16), 2nd CPU is needed			
Memory protection	ECC, memory mirroring, lockstep, and memory sparing			
RAID controller	RAID controller	Drive type	RAID support	Compatible models
	Onboard RAID110i	6Gbs SATA	0/1/10, 5 with optional key	4x3.5" HS/ES, 8x2.5" HS
	RAID500 PCIe	6Gbs SAS/SATA	0/1/10, 5/50 with optional key	4x3.5" HS, 8x2.5" HS
	RAID520i PCIe	12Gbs SAS/SATA	0/1/10, 5/50 with optional key	4x3.5" HS/ES, 8x2.5" HS
	RAID710 PCIe (1GB memory)	6Gbs SAS/SATA	0/1/10/5/50/6/60	4x3.5" HS, 8x2.5" HS
	RAID720i PCIe	12Gbs SAS/SATA	0/1/10/5/50, 6/60 with optional cache	4x3.5" HS/ES, 8x2.5" HS
		Optional cache for RAID 710: CacheVault flash cache with super capacitor, CacheCade Pro, or FastPath. Optional cache for RAID 720/AnyRAID 720i and 720ix: 1GB read-only memory or 1GB/2GB/4GB flash with super capacitor. Flash options include CacheVault, CacheCade Pro, and FastPath. 720ix must have cache. <i>Note: RAID 50 and 60 are available on 8 x 2.5" models only.</i>		
Disk drive bays	Up to 4x3.5" hot-swap, 4x3.5" easy-swap, or 8x2.5" hot-swap disk bays on front. Supports external RDX tape drive via USB.			
Maximum internal storage	3.5" model: up to 32TB with 7.2K SATA or SAS HDD, up to 7.2TB with 10K SAS HDD, up to 2.4TB with 15K SAS HDD, or up to 6.4TB with SATA SSD. 3.5" ES model: up to 12TB with 7.2K SATA, up to 24TB with 7.2K SAS. 2.5" model: up to 16TB with 7.2K SATA HDD, up to 14.4TB with 10K SAS HDD, up to 4.8TB with 15K SAS HDD, or up to 12.8TB with SATA or SAS SSD			
SD module	Up to 2 SDHC flash cards via optional SD module, 8GB or 32GB each			
Optical drive	Optional one 9.5mm optical, DVD-ROM or DVD±RW.			
Network interfaces	One dedicated management port, two Gigabit Ethernet ports (RJ-45). Supports optional discrete network adapters via PCIe slots			
Security features	Power-on and administrator password. Optional TPM (TCG 1.2-compliant) Supports ThinkServer System Manager (TSM), optional TSM Premium. UEFI. Onboard Aspeed AST2400 graphics/management processor, IPMI 2.0-compliant baseboard management controller (BMC). Control Panel LEDs shows the status of power, ID, network, system. Supports ThinkServer management software: Diagnostics, Deployment Manager, Energy Manager, System Manager, Partner Pack for VMware vCenter and Microsoft System Center Operations Manager, Power Planner			
Systems management				

Components	Specification																
Operating systems supported	Microsoft Windows Server 2016/2012 R2/2012/2008 R2. Windows Small Business Server 2011. Red Hat Enterprise Linux 6.5/6.6/7. SUSE Linux Enterprise Server 11. VMware vSphere (ESXi) 5.1 P5/5.5 U2/6.0																
Base warranty	1 or 3-year limited onsite service with 9x5/NBD																
Power supply	Up to two redundant hot-swap 450W/550W/750W power supplies. 450 W is 80 PLUS Gold qualified. 550W is 80 PLUS Platinum qualified. 750W is 80 PLUS Platinum or Titanium qualified. 750W Titanium is 200V - 240V, others are 110V - 240V.																
	<table><tr><td>Disk bay configuration</td><td colspan="3">PSU requirements</td></tr><tr><td></td><td>450W</td><td>550W</td><td>750W</td></tr><tr><td>4x3.5"</td><td>•</td><td>•</td><td>•</td></tr><tr><td>8x2.5"</td><td>•</td><td>•</td><td>•</td></tr></table>	Disk bay configuration	PSU requirements				450W	550W	750W	4x3.5"	•	•	•	8x2.5"	•	•	•
	Disk bay configuration	PSU requirements															
		450W	550W	750W													
4x3.5"	•	•	•														
8x2.5"	•	•	•														
Graphics	Onboard Aspeed AST2400 with 16MB memory, one DisplayPort on front, one VGA on rear.																
Front ports	Two USB 2.0. One DisplayPort (one VGA on E5-2600 v4 models instead)																
Rear ports	One VGA, two USB 3.0, one RJ-45 (dedicated mgmt), two ethernet, one serial (9-pin)																
Cooling	6 (5+1, dual processors) or 4 (3+1, single processor) fans, non-hot swap																
Noise emissions	Operating: < 6.5 Bels. Idle: < 5.4 Bels (Maximum configuration)																
Environmental specification	Temperature - operating	50 °F to 95 °F (10 °C to 35 °C)															
	Temperature - non operating (no package)	-10 °C to 60 °C															
	Temperature - non operating (with package)	-40 °C to 70 °C															
	Altitude - operating	(Unpressurized): 0-10000ft (0-3048m)															
	Humidity - operating	8%~90%, non-condensing															
	Humidity - storage (with package)	8%~90%, non-condensing															

Expansion slots



Up to two PCIe 3.0 x 16 slots:

Slot 1	PCIe 3.0 x16, half length, full height, by CPU1
Slot 2 for dual processors model	PCIe 3.0 x16, low-profile, half length, requires 2nd riser card and 2nd CPU
Slot 2 for single processor model	PCIe 3.0 x16 (x8 electrical), low-profile, half length, by CPU1, requires 2nd riser card

For a list of all supported options, please see https://download.lenovo.com/pccbbs/options_iso/ocm_september_2016_thinkserver.xlsx sheet

Model	70QM000JEA
Product	ThinkServer RD350
Region	EMEA
Machine Type	70QM
TopSeller	TopSeller
Processor	1xE5-2630 v4 10C/2.2GHz/20MB/85W/DDR4-2133
2nd CPU	4XG0G89074
Memory	1x16GB RDIMM DDR4-2400 ECC
RAID Controller	520i PCIe
Disk Bays	8x2.5" HS
Storage	Open
Slots	1xFHHL
Optical	9.5mm DVD±RW
Add-on NIC	None
TPM	None
System Management	TSM
Operating System	None
Warranty	3-year
Power Supply	450Wx1 Gold
Ann Date (mm/yy)	04/16



