Product datasheet

Specifications



Power Cord, Locking C19 to BS1363A (UK), 3.0m

AP8756

EAN Code: 0731304279808

Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

Main

Product or component type	Power cord
Input current limits	13 A
Input Connection Type	BS1363A British
Max current draw	13 A
Max line current	13 A
Number of cables	1
Cable length	2.9 m
Power cable length	3.05 m

Complementary

Mounting preference	No preference
Mounting mode	Not rack-mountable
Height	230 mm
Width	230 mm
Depth	50 mm
Net weight	0.44 kg

Environmental

Product certifications	BSI 1363 VDE
Relative humidity	20…80 %
Storage Relative Humidity	20…80 %
Ambient air temperature for storage	-20…70 °C
Storage altitude	0…15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	0…70 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	5 cm
Package 1 Length	23 cm
Package 1 Weight	0.44 kg
SCC14	10731304279805

Logistical informations

Country of origin	CN

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**53 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.2 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**50 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.8 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
SCIP Number	**1cdb2fed-a06f-4574-913d-8df8e70936b2**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
Halogen-free status	**Product contains halogen above thresholds**

Use Again

Repack and remanufacture

Recyclability potential, in %	**30**
End of life manual availability	**End of Life Information**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**