PCIe x1 VL805 3-USB3.0 + RTL8153 Network Extend Card



P/N.: MC-PCIEX1-VL805+AX88179

USER Manual

EN ver2.0

Features:

Complies with PCI Express Base Specification Revision 2.0
Complies with Universal Serial Bus 3.0 specification Revision 1.0
Backward compatible to USB 2.0 and PCI-Express 1.0
4-pin power connector for extra power
Support Windows XP/Vista/7/8/8.1(32/64 bit)

USB3.0 Interface:

Supports Low-speed (1.5Mbps) / Full-speed (12Mbps) / High-speed (480Mbps) / Super-speed (5Gbps)
Max. 5V/900mA power output to each USB 3.0 Port
Fully plug, play and hot plug compatible
Support Windows XP/Vista/7/8/8.1(32/64 bit)

RJ45 Port:

Fully compliant with IEEE802.3,IEEE802.3u. IEEE802.3az
Supports Full Duplex flow control
Supports WAKE -ON-LINE and remote wakeup.
10/100/1000M data auto-negotiation
Integrated 10/100/1000M transceivers LED lights
USB3.0 bandwidth up to 5Gbps,Users can through the RJ45 interface to enjoy the Gigabit Network
Onboard with hardware drivers, easy to used
Supported operating system: XP/Vista/Win7/Win8/Win8.1 32/64bit.

System Requirements

Windows® XP/Vista/7 /8(32/64 bit)
PCI-Express enabled system with an available PCI-Express X1 slot

Package Contents

1 x PCI Express USB3.0＆Network Card
1 x Driver CD
1 x User Manual

Hardware Installation

1. Turn off your computer and devices connected to it.
2. Remove the computer's cover ,Refer to your computer user's manual for more details
3. Find an unused PCIe slot and remove the metal bracket.Save the bracket screw for later use
4. Align the card horizontally with respect to the PCIe slot and insert it into the slot firmly and evenly,Take care not to force it into the slot ,once you have properly positioned the card into the slot , ,connecting the Big-4P power to supply USB power.

Micro Connect®
Reliable Connectivity

Driver Installation

Partition of USB3.0 port ,For Windows® XP/Vista/Win7/Win8 (32/64 bit)

1. 1. Please insert the CD driver bound with USB 3.0 4-Port PCI Express Card into your CD-ROM Drive.
2. 2. At the Windows desktop, click **Start**, **Run**.
3. 3. Type"USB3.0 VL805-806\V3.10C_WHQL **\Setup.exe"**, click **OK**.
4. 4. Follow the on-screen instructions to complete the installation.

Partition of RJ-45 port ,For Windows® XP/Vista/Win7/Win8 (32/64 bit)

1. When you have installed the USB3.0 drivers, Windows will detect the network card and attempt to install driver for it.
2. At the end ,when you open "my computer" or "computer", you will seems an new CD-ROM drive,
3. Please locate and double-click on the "**Setup.exe** "file in the CD to launch the install program.
4. Double-click the "setup.exe", the program will following the system auto installing drivers

To Verify Windows® Driver Installation

Click on the **"Device Manager"** tab in System Properties, which you access from the Windows Control Panel. You should see a "VIA USB 3.0 Root Hub" and a "**VIA USB eXtensible Host Controller**" under the "**Universal Serial Bus controllers**" item,and You should see a "**Realtek USB GBE Family Controller**" under the "Network Adapter"

Support

More information and settings please refer to the User Guides or you can contact us.