


BP 2 CISTERN

The BP 2 Cistern with robust stainless steel housing is the ideal immersion pressure pump for garden watering using rain water from a cistern. Includes hose connection set and float switch.



Order no. 1.645-420.0

- Pump casing, threaded connectors and convenient stainless steel carrying handle
- ¾"- and 1" hose connection piece, including check valve and hose clip
- Float switch with flexibly adjustable switching level

Technical data

EAN code		4039784873292
Max. motor rating	W	800
Max. flow rate	l/h	< 5700
Delivery head	m	32
Pressure	bar	max. 3.2
Immersion depth	m	max. 7
Delivery temperature	°C	max. 35
Connection thread		G1
Power cable	m	10
Voltage	V	230
Frequency	Hz	50
Colour		silver
Weight without accessories	kg	9.9
Weight incl. packaging	kg	11.2
Dimensions (L × W × H)	mm	130 × 130 × 475

Equipment

Integral non-return valve	■ ■
Stainless steel pump casing and threaded connections	■
Hose connection piece in 1", ¾" with hose clip	■
Float switch	■ ■
Robust stainless steel handle	■
Integrated prefilter	■
Simple definition of switching level	■
■ Included in the scope of supply.	■



Stainless steel pump casing, threaded connections and carrying handle

- Increased lifespan and shock resistance, as well as secure transport and simple handling.



Includes pump connecting piece and check valve

- Fast connection of 3/4" and 1" hoses to the pump.



Integrated prefilter

- Protects the pump against contamination and thus increases its lifespan and functional reliability.

ACCESSORIES FOR BP 2 CISTERN 1.645-420.0



		Order no.	Description	
ADAPTERS / CONNECTORS				
Adapter connection	1	6.997-473.0	With the help of the connection adapter, a pump with internal thread can be connected quickly and safely to a water connection.	■
Pump adapter including check valve, small	2	6.997-359.0	Pump adapter with check valve for vacuum-resistant connection of suction hoses to pumps (e.g. garden pumps and high-pressure pumps for domestic use).	■
2-way connection adapter for pumps, G1	3	6.997-474.0	With the help of the 2-way connection adapter, a pump with internal thread can be connected quickly and safely to two water connections.	□
Connection kit Basic	4	6.997-358.0	Connector set for connecting water hoses to garden pumps and high-pressure pumps for domestic use. For easy and perfect hose and pump connection.	□
Premium pump connector set	5	6.997-340.0		□
MISCELLANEOUS				
Dry-run cut-out for pumps *Socket Type E (CEE7/5)	6	6.997-546.0	The dry-run protection protects garden pumps, submersible pressure pumps and home pumps against damage. The pump is automatically switched off if there is no water running through it.	□
Electronic pressure switch with dry-run cut-out for pumps *Socket Type E (CEE7/5)	7	6.997-549.0	The electronic pressure switch automatically switches the pump on and off again as required. An additional dry-run protection protects the pump against damage by automatically switching it off when there is no water running.	□
Dry-run cut-out for pumps	8	6.997-355.0	Dry-running protection protects garden pumps, submersible pumps and high-pressure pumps against damage. Float switch automatically starts and stops the pump and prevents dry running.	□
Electronic pressure switch with dry-run cut-out for pumps	9	6.997-357.0	Electronic pressure switch automatically starts/stops the pump on demand. Float switch automatically starts and stops the pump and prevents dry running.	□

■ Included in the scope of supply. □ Available accessories. ○ Detergents.