

## E1 Outdoor PoE

### 4K PTZ PoE Camera with Person/Vehicle Detection, Auto Tracking and 3X Optical Zoom

- Pan, Tilt & 3X Optical Zoom
- 4K 8MP Ultra HD
- Auto Tracking

## Specifications

Video & Audio	
Image Sensor	1/2.8" CMOS sensor
Resolution	3840x2160 (8 Megapixels) @25fps
Lens	f=2.8-8mm, Max: F1.6/IR CUT
Video Format	H.265/H.264
Field of View	Horizontal: 90°-50° Vertical: 53°-30°
Zoom	3x optical zoom
Pan/Tilt Angle	Pan: 355°, Tilt: 50°
Day & Night	IR-cut filter & auto-switching
Infrared Night Vision	12 Meters (LED: 10pcs/1.4w/14mil/850nm)
Spotlight	12m (40ft) (4pcs, 3.3w, 6500K)
Audio	Built-in microphone and speaker
Interface	
Power	DC12V/1A & PoE (IEEE 802.3af)

System	Reset Button
Network	One 10M/100Mbps; RJ45
Storage	Supports Max. 512GB microSD card; Reolink NVR
<b>Software</b>	
Frame Rate	2-25FPS (Default: 25FPS)
Code Rate	Main stream: 2048Kbps - 8192Kbps (default: 6144Kbps) Sub stream: 64Kbps - 512Kbps (default: 256Kbps)
Browsers Supported	Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: IOS, Android
Smart Alarm	Motion detection; AI detection
Recording Modes	Motion-triggered recording; Scheduled recording, 24/7 recording
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P, ONVIF
User Access	20 users (1 admin account & 19 user & administrator accounts); up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Linked Devices	YES
Work with	Google Assistant
<b>Working Environment</b>	
Operating Temperature	-10°C~55°C (14°F~131°F)
Operating Humidity	10% ~ 90%
Weatherproof	IP65
<b>Size &amp; Weight</b>	
Dimensions	Φ90*120mm
Weight	458g
<b>Warranty</b>	

Limited Warranty

2-year limited warranty. For support, visit <https://support.reolink.com/hc/en-us/>.

## Gallery & Specs



1. Daylight Sensor
2. Spotlight
3. Lens
4. IR LED
5. Status LED



1. microSD Card Slot
2. Power
3. Network
4. Power Cable
5. Speaker

[www.reolink.com](http://www.reolink.com)