

9 m (30 ft.) Active USB 2.0 A to B Cable

**Product ID:** USB2HAB30AC



This 30-foot USB A to B cable features one USB type-A connector and one USB type-B connector, providing a high-quality connection to USB 2.0 peripherals.

This USB cable is expertly designed with top quality materials, incorporating an equalizing chip, which enables it to perform beyond the limits of standard USB cables and communicate with peripherals up to 30 ft. away.

USB2HAB30AC is backed by a StarTech.com 2-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility



## Applications

- Connecting USB 2.0/1.1 devices up to 30ft away to a computer

## Features

- Built-in equalizing chip enables USB 2.0 connections spanning 30ft

---

### Hardware

Warranty

2 Years

Connector Plating	Nickel
Cable Jacket Material	PVC - Polyvinyl Chloride
Cable Shield Material	Aluminum-Mylar Foil with Braid

---

**Performance**

Maximum Cable Length	29.5 ft [9 m]
Type and Rate	USB 2.0 - 480 Mbit/s

---

**Connector(s)**

Connector A	1 - USB 2.0 Type-A (4 pin, 480Mbps)
Connector B	1 - USB B (4 pin)

---

**Special Notes / Requirements**

Note	USB2HAB30AC draws a maximum of 70mA for powering internal active circuitry
------	--

---

**Environmental**

Operating Temperature	0-75C
Storage Temperature	5-35C
Humidity	60-90%

---

**Physical Characteristics**

Color	Black
Wire Gauge	28 AWG
Cable Length	29.5 ft [9 m]
Product Length	29.5 ft [9.0 m]
Product Width	1.0 in [2.6 cm]
Product Height	0.6 in [1.4 cm]
Weight of Product	14.3 oz [404 g]

---

**Packaging Information**

Package Quantity	1
------------------	---

Package Length	5.7 in [14.4 cm]
Package Width	5.6 in [14.1 cm]
Package Height	2.8 in [7.0 cm]
Shipping (Package) Weight	1.0 lb [0.5 kg]

---

**What's in the Box**

Included in Package	1 - 9m/30ft High Speed Certified USB 2.0 Cable
---------------------	--

---

**Warranty Information**

Warranty	2 Years
----------	---------

---

***\*Product appearance and specifications are subject to change without notice.***