Brother ADS-1300 skannrar ADF-skanner 600 x 600 DPI A4 Vit



Märke : Brother

Produktkod: ADS-1300

Product name : ADS-1300

- Skanna upp till 30 sid/min.
- Automatisk dokumentmatare för 20 ark (ADF)
- Ström direkt via USB Type-C.
- Kontrollera upp till 3 genvägar för skanningsaktivitet direkt från enheten
- Dedikerad plast ID-kortplats

Ström direkt från din bärbara dator med USB Type-C, så att du kan skanna, spara och dela där det är mest bekvämt för dig.



Brother ADS-1300 skannrar ADF-skanner 600 x 600 DPI A4 Vit:

Gör det enkelt att scanna dokument varje dag med den kompakta och bärbara ADS-1300-dokumentscannern.Skanna och spara dina pappersdokument var du än arbetar. Allt ifrån affärsdokument till medicinska formulär, anslut en gång till din bärbara dator så kan du skanna och lagra data säkert och ha omedelbar tillgång när du behöver det.Skanna till PC, moln, USB-värdPDF-redigeringsprogram ingårTillvalsfack för pappersutmatning finns - se OT1001C*Se datablad för detaljerad teknisk information

Skanning	
Maximal skanningsstorlek *	215,9 x 355,6 mm
Optisk skanningsupplösning *	600 x 600 DPI
Förstärkt scannerupplösning	1200 x 1200 DPI
Dubbelsidig skanning *	✔
Gråskalenivå	256
ADF Scan-hastighet (b / w, A4)	7 ppm
Design	
Skanningstyp *	ADF-skanner
Produktens färg *	Vit
Kontrolltyp	Knappar
Inbyggd display *	✘
Prestanda	
Skanning till	PC
Scanningsdrivrutiner	ICA, SANE, TWAIN, WIA
Pappershantering	
Mediatyper som stöds vid scanning	Visitkort, Plastkort, Tjockt papper, Plain paper, återvunnit papper, Tunt papper
Högsta ISO A-seriestorlek *	A4
Korttjocklek (max)	1,24 mm
Pappersfackets mediavikt	51,8 - 128 g/m ^

Anslutningar	
USB-port *	✔
USB-anslutning	USB Type-C
Strömtillförsel	
Nätaggregatstyp *	USB
Strömförbrukning (vanlig)	11 W
Strömförbrukning i avslaget läge	0,1 W
Vikt & dimension	
Bredd	288 mm
Djup	101 mm
Höjd	85 mm
Vikt	1,37 kg
Förpackning	
Förpackningens bredd	158 mm
Låddjup	200 mm
Förpackningens höjd	369 mm
Vikt inkl. förpackning	2,36 kg
Förpackningens innehåll	
Kabel inkluderad	USB
Miljökrav	
Temperatur vid drift	5 - 35 ° C
Intervall för relativ operativ luftfuktighet	20 - 80%



0012502674221



012502674221



4977766832212



4977766832229

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 20-NOV-2026. Prints or copies of Information are only valid on the printed Publication date