

2-portars Gigabit PCIe-kortadapter för nätverkskort, 10/100/1 000 Mbps PCI Express NIC, Dual Realtek RTL8111H, kompatibelt med Windows och Linux, TAA-kompatibel

Produkt ID: ST1000SPEXD4T



This TAA-compliant Gigabit Ethernet card adds two gigabit Ethernet interfaces to a desktop or server.

This 2-port network interface card is plug-and-play compatible, with drivers that auto-install on major operating systems such as Windows, Windows Server, and Linux. It is compatible with Intel and AMD hardware platforms equipped with PCI Express x1, x2, x4, x8, or x16 slots.

This network card features link speed and activity LED indicators for visual network speed verification and issue diagnosis.

This PCIe network adapter supports 9K jumbo frames to minimize packet overhead, Wake-on-LAN (WoL) for remote system booting, auto-negotiation between 10/100/1000Mbps, and VLANs for streamlined network management.

The PCI Express NIC includes a pre-installed standard-profile bracket for full-sized desktops and servers, as well as a low-profile bracket for compatibility with small form-factor computers.

Certifikat, rapporter och kompatibilitet



Användning

- Add two gigabit Ethernet ports to a workstation or server computer, for redundancy or bridging

Funktioner

- **TAA-COMPLIANT GIGABIT ETHERNET CARD:** Network Card with dual Realtek RTL8111H chips adds two gigabit Ethernet interfaces to a desktop/server; Features link speed/activity LED indicators allowing users to visually diagnose issues and confirm network speeds
- **PLUG & PLAY COMPATIBILITY:** 2-Port Network Interface Card drivers auto-install in most major operating systems including Windows, Windows Server, and Linux; Works with Intel and AMD hardware platforms that have a PCI Express x1, x2, x4, x8, or x16 slot
- **PERFORMANCE & MANAGEMENT:** 10/100/1000Mbps PCIe Network Adapter Card features independent Ethernet controllers that support 9K jumbo frames to reduce packet overhead, Wake-on-LAN (WoL) for remote system booting, and VLANs for efficient network management
- **UNIVERSAL FIT:** PCI Express NIC comes with a pre-installed standard-profile bracket for full-sized desktops and servers, and it includes a low-profile bracket for compatibility with small form-factor computers
- **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, this 2-port network card is backed for 2-years, including free lifetime 24/5 multi-lingual technical assistance

Hårdvara

Garantipolicy	2 Years
Portar	2
Busstyp	PCI Express
Korttyp	Standardprofil (inkl. LP-fäste)
Porttyp	Inbyggd på kort
Industristandarder	IEEE 802.3
	IEEE 802.3u
	IEEE 802.3x
	IEEE 802.3ab
Chipset-ID	Realtek - RTL8111H

ASMedia - ASM1182

Prestanda

Wake On Lan	Ja
Maximal dataöverföringshastighet	1 000 Mbps
Kompatibla nätverk	10/100/1000 Mbps
Auto MDIX	Ja
PXE	Nej
Jumbo Frame Support	9K max.
Promiscuous Mode	Ja

Kontakt(er)

Externa portar	2 - RJ-45
Värdkontakter	1 - PCI Express x1

Mjukvara

OS-kompatibilitet	Windows 8/8.1, 10, 11 Windows Server 2016, 2019, 2022 Linux 2.4.x and up - LTS Versions only
-------------------	--

Indikatorer

LED-indikatorer	2 - Right LED: Link/Activity Solid green: Active link Flashing green: Activity Off: No active link 2 - Left LED: Link Speed Solid green: 1Gbps link Solid orange: 10/100Mbps link
-----------------	---

Ström

Power Source	Bus driven
--------------	------------

Miljö

Drifttemperatur	5°C to 70°C (41°F to 158°F)
Förvaringstemperatur	0°C to 80°C (32°F to 176°F)
Luftfuktighet	10% ~ 80% (non-condensing)

Utseende

Färg	Svart
Produktlängd	3.0 in [7.5 cm]
Produktbredd	2.4 in [6.1 cm]
Produkthöjd	0.7 in [1.8 cm]
Produktvikt	1.7 oz [47.0 g]

Förpackning

Package Length	6.7 in [17.0 cm]
Package Width	5.6 in [14.2 cm]
Package Height	1.2 in [3.0 cm]
Fraktvikt (förpackning)	3.9 oz [111.2 g]

Vad det är i lådan

Ingår i paketet	1 - PCIe Card
	1 - Lågprofilsfäste
	1 - Quick-Start Guide

* Produkters utseende och specifikationer kan komma att ändras utan förvarning.