

Belt Sander LXT®

DBS180

18V • 600 – 1 700 m/min • 9 mm

Narrow tool for detail work

A light and easy-to-use belt sander powered by 18V LXT® battery. The belt speed can be adjusted between 600 – 1 700 m/min. This is an ideal tool for finishing, burr removal and working in confined areas. Movable LED light.





Technical specifications

Nominal Battery Voltage Voltage LXT Brushless Motor Belt Speed Belt Size

Sound Pressure Level (L_{pA})

Noise Uncertainty (K Factor)
Vibration Level (3 axes)
Vibration Uncertainty (K Factor)
Tool weight with battery (EPTA)
Product Dimensions (L x W x H):

Product net weight

Vacuum cleaner connection Ø in / out

18 V √

600 - 1700 m/min 9 x 533 mm

77 dB(A)

3 dB(A) 2,5 m/s² 1,5 m/s² 1,8 - 2,1 kg 500 x 96 x 116 mm

1,4 kg 17/22 mm

User benefits

- Electric brake for maximum productivity and increased operator safety
- Variable speed control dial enables user to match the speed to the application
- Lock-on button for continuous operation
- Brushless maintenance-free and long-life motor
- Movable LED
- Compact storing because of wide range of arm motion
- High power: same efficiency as corresponding AC model
- Battery protection system automatically shuts off power when the battery level is low

Link to product - www.makitauk.com



Related products

Optional AC

122652-8

Dust nozzle Assembly

125159-3

Arm Assembly 13mm

198043-5

Grip 36 set

BL1830B

Battery LXT® 3,0 Ah

BL1850B

Battery LXT® 5,0 Ah

125158-5

Arm Assembly 9 mm

___ 140W02-3

Grip Base Complete

BL1820B

Battery LXT® 2,0 Ah

BL1840B

Battery LXT® 4,0 Ah

BL1860B

Battery LXT® 6,0 Ah

Other

User manual

Parts drawing