



NT 70/3 Me Tc

3-moottorinen märkäkuivaimuri kohteisiin, joissa tarvitaan suurta imutehoa.

1 Integroitu tarvikkeiden säilytys

- Suojapuskuri jossa tarvikkeiden säilytystilat.

3 Kipattava säiliö

- Quick and easy: the container tilts back for easy emptying.

2 Ergonominen työntökahva

- Laitteen siirtely on helppoa ergonomisen työntökahvan avulla.

NT 70/3 Me Tc

- Ergonominen työntökahva
- Ruostumaton terässäiliö

Tekniset tiedot

Tuotenumero		1.667-274.0
EAN koodi		4039784725423
Ilman läpivirtaus	l/s	3 x 74
Alipaine	mbar / kPa	254 / 25,4
Säiliötilavuus	l	70
Maks. ottoteho	W	3600
Varusteiden halkaisija ID 51/61		ID 40
Virtajohdon pituus	m	10
Äänenvoimakkuus	dB(A)	79
Säiliön materiaali		ruostumatonta terästä
Moottoreiden lukumäärä		3
Taajuus	Hz	50-60
Jännite	V	220-240
Paino	kg	29,9
Mitat (p x l x k)	mm	510 x 645 x 990

Laite

Imuletku	m	4	Turvallisuusluokitus	II
Imuputki	kpl / m	2 x 0,5 / Metalli	Säiliön pyörä seisontajarrulla	■
Lattiasuulake markä- ja kuivaimurointiin	mm	400		
Rakosuulake		■		
Patruunasuodatin		■		
Tyhjennysletku		■		
Ruostumaton terässäiliö		■		
Kipattava säiliö		■		
Imukahva		■		
Patruunasuodatin		Paperi		
Työntöaisa		■		

■ Toimituksen mukana.

NT 70/3 ME TC

1.667-274.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Patruunasuodatin, paperi								
Patruunasuodatin NT 70 x	1	6.907-038.0	1 kpl				Paper cartridge filter (M BIA-C dust class M), suitable as a main filter for dry and wet pick up.	■
Lattiasuulakkeet								
	2	2.889-117.0	1 kpl	ID 40		400 mm		■
LAITOSSUUTIN GRD 370	3	6.903-018.0	1 kpl	ID 40		370 mm	All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN40	4	6.906-383.0	1 kpl	ID 40		450 mm	All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN 35	5	6.906-384.0	1 kpl	ID 35		370 mm	All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
Rakosuulakkeet								
RAKOSUUTIN NW 40	6	6.903-033.0	1 kpl	ID 40	290 mm		Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	■
RAKOSUUTIN, NW 35	7	6.900-385.0	1 kpl	ID 35	210 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	□
RAKOSUUTIN METALLISTA	8	6.900-922.0	1 kpl	ID 35	500 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□
RAKOSUUTIN	9	6.905-817.0	1 kpl	ID 40	400 mm		Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□
Imutangot metallia								
Imutanko, 0,5m, metallia/ ID 40	10	6.900-275.0	1 kpl	ID 40	0,55 m		Chromium-plated metal suction tube (DN 40, 1x0.5 m), standard for virtually all two-motor industrial vacuum cleaners. Optional for industrial single-motor NT vacuum cleaners with DN 40 suction hose.	■
IMUPUTKI NW 35, 0,5	11	6.900-514.0	1 kpl	ID 35	0,5 m		Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	□
Imuletkut täydellinen (Clip-system)								
Imuletku 4 m, (Clip-system)	12	4.440-678.0	1 kpl	ID 40	4 m		4 m electrically non-conductive suction hose with bend, bayonet at vacuum end and C 40 clip connection at accessory end. Without module.	■
Imuletku 16 m (clip-system)	13	4.440-784.0	1 kpl	ID 40	16 m		16 m suction hose (C-DN 40) with bayonet and straight adapter.	□
Karkeanliansuodatin veden imurointiin								
Vaahdotuovisuodatin	14	2.889-083.0	1 kpl				Not suitable for dry vacuuming.	□
Kangassuodatin								
Membraanisuoatatin /polyester-fleece	15	6.904-282.0	1 kpl				Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	□
Paperinen pölypusssi (kaksinkertainen)								
PÖLYPUSSI NT 65/2 Eco	16	6.904-285.0	5 kpl				5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	□
Muovisäkit								
Muovisäkki NT 7xx 110 kpl	17	6.900-698.0	10 kpl				PE plastic sack.	□

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 70/3 ME TC

1.667-274.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Erikoispölypussi, märkäimurointi								
Erikoispölypussi märkäimurointiin	18	6.904-252.0	5 kpl				Approved for dust class L, general cleaning, wet and dry, tear-resistant.	☐
Taivutetut imutangot, rosteria								
Taivutettu tanko DN 35, RST	19	6.903-141.0	1 kpl	ID 35			Stainless steel and crooked, ID 35	☐
Taivutettu tanko DN 40, RST	20	6.902-079.0	1 kpl	ID 40			Stainless steel and crooked, ID 40	☐
Taivutettu imutanko, muovia								
Taivutettu tanko DN 35, muovi	21	5.031-718.0	1 kpl	ID 35			Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	☐
Taivutettu tanko DN 35, muovi, sähköä johtava	22	5.031-939.0	1 kpl	ID 35			Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	☐
Taivutettu tanko DN 40, muovi, sähköä johtava	23	5.032-427.0	1 kpl	ID 40			Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	☐
Taivutetut imutangot, metallia								
Taivutettu tanko, metallia ID 35	24	6.900-519.0	1 kpl	ID 35			Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el.).	☐
Taivutettu tanko, metallia ID 40	25	6.900-276.0	1 kpl	ID 40			Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el.).	☐
Autonimurointisuuilakkeet								
AUTOSUUTIN,JATKOSSA 6.906-255	26	6.900-952.0	1 kpl	ID 40		90 mm	Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	☐
Käytäväsuulakkeet								
Käytäväsuulake	27	4.130-432.0	1 kpl	ID 40		644 mm	Vacuuming larger Areas in connection with NT 70/1; NT 70/2 or NT 70/3 versions only.	☐
Imusuulake, kumikärki 45°								
Kumisuulake, DN 35 45° kärki	28	6.902-104.0	1 kpl	ID 35	220 mm		45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
Kumisuulake, DN 40, 45° kärki	29	6.902-105.0	1 kpl	ID 40	220 mm		45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
Putkisuulakkeet								
PUTKISUUTIN 100 MM	30	6.903-035.0	1 kpl	ID 35			Plastic, pipe diameter 100 mm	☐
PUTKISUUTIN 200 MM	31	6.903-036.0	1 kpl	ID 35			Plastic, pipe diameter 200 mm	☐
Harjasuulakkeet								
HARJASUUTIN NIVELÖITY 35mm	32	6.903-862.0	1 kpl	ID 35		70 mm	Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.	☐
HARJASUUTIN	33	6.903-887.0	1 kpl	ID 32		70 mm	Rotatable suction brush (DN 32 plastic) with PA bristles, 70x45 mm. Only for BV and T vacuum cleaners.	☐
Imutangot, ruostumaton teräs								
Imutanko, 0,5 m RST DN 40	34	6.902-081.0	1 kpl	ID 40	0,5 m		Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	☐
Imutanko, 1 m RST DN 40	35	6.906-531.0	1 kpl	ID 40	1 m		Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	☐
Imutanko DN 35	36	6.902-154.0	1 kpl	ID 35	0,5 m			☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 70/3 ME TC

1.667-274.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Korjaussarjat								
Korjaussetti	37	2.639-873.0	1 kpl	ID 40			Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	☐
	38	2.862-038.0	1 kpl	ID 61			Suction hose repair kit. Optional for all NT 65/2 and 72/2, NT 993 I, NT 802 I.	☐
Imuletkut (Clip-system)								
Imuletku 10 m clip-system	39	6.906-279.0	1 kpl	40	10 m		10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.	☐
Imuletku 4 m clip-system	40	6.906-321.0	1 kpl	40	4 m		4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	☐
Imuletku 4 m, clip-system, sähköä johtava	41	6.906-546.0	1 kpl	40	4 m		Sähköä johtava, 4 m imuletku bajonet-liitännällä ja C 40 clip-system pikakiinnityksellä. Mutka ja adapteri eivät sisälly toimitukseen. Huom! Ilman erillistä sovitinta, imuletku ei ole yhteensopiva 1-moottoristen imureiden vakiovarusteiden kanssa.	☐
Imuletku 16 m, clip-system	42	6.906-635.0	1 kpl	40	16 m		With bayonet and clip connection.	☐
Imuletku 4 m, clip-system, sähköä johtava	43	6.906-877.0	1 kpl	40	10 m		Suction hose with bayonet coupling, electrically conductive.	☐
Imuletkut täydellinen								
Imuletku 4 m	44	4.440-264.0	1 kpl	ID 61	4 m		4-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.	☐
Imuletku 10 m	45	4.440-467.0	1 kpl	ID 61	10 m		10-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.	☐
Imuletku 4 m, öljynkestävä	46	4.440-613.0	1 kpl	ID 61	4 m		Oil-resistant.	☐
Imuletku 4 m, sähköä johtava	47	4.440-616.0	1 kpl	ID 61	4 m			☐
Imuletku 4 m	48	4.440-263.0	1 kpl	ID 40	4 m		Electrically non-conductive 4.0m standard suction hose with bayonet at vacuum end and DN 40 cone at accessory end.	☐
Imuletku 4 m, öljynkestävä	49	4.440-303.0	1 kpl	ID 40	4 m		Oil-resistant	☐
Imuletku 10 m	50	4.440-463.0	1 kpl	ID 40	10 m		Electrically non-conductive 10.0m standard suction hose with bayonet at vacuum end and DN 40 cone at accessory end.	☐
Imuletku 10 m, sähköä johtava	51	4.440-466.0	1 kpl	ID 40	10 m		Electrically conductive, 10.0m, ID 40	☐
Imuletku 10 m, öljynkestävä	52	4.440-612.0	1 kpl	ID 40	10 m		Oil-resistant.	☐
Sovitin-kappaleet								
Letkujen liitoskappale	53	6.902-077.0	1 kpl	ID 32			Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	☐
	54	6.900-286.0	1 kpl	ID 40			Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	☐
	55	6.902-078.0	1 kpl	ID 61				☐
Jatkoletkut (Clip-system)								
Jatkoletku (clip-system) 2,5 m	56	6.906-344.0	1 kpl	ID 40	2,5 m		2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	☐
muut								
CS 40 Me	57	2.863-026.0	1 kpl					☐
Y-liitinsetti								
Y-kappale, muoviva	58	2.637-217.0	1 kpl	ID 35			Plastic distributor - suitable for NT vacuum cleaners.	☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 70/3 ME TC

1.667-274.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus	
Sovitin C ID, antistaattinen									
Liitoskappale C-DN35 (sähköä johtava)	59	5.407-112.0	1 kpl	ID 35				C 35 hose connector for DN 35 accessory, electrically conductive.	☐
Liitoskappale C40-DN35	60	5.407-109.0	1 kpl	ID 40				Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	☐
Liitoskappale C-DN40	61	5.407-111.0	1 kpl	ID 40				C 40 hose connector for DN 40 accessory, electrically conductive.	☐
Sovitin (putkisuutin)									
Sovitin DN 40-61	62	5.453-019.0	1 kpl	ID 40				From DN 40 to DN 61: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	☐
Supistin									
Supistin C40	63	5.407-108.0	1 kpl	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	☐
BUSHING	64	5.407-113.0	1 kpl	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	☐
Supistin (putki - suutin)									
Supistin DN40 - DN35	65	6.902-017.0	1 kpl	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	☐
Supistin DN35 - DN32	66	6.902-072.0	1 kpl	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	☐

■ Toimituksen mukana. ☐ Saatavilla olevat varusteet.

NT 70/3 ME TC
1.667-274.0



		Tuotenumero	Pituus		Määrä		Kuvaus	
Sekalaiset								
Jatkojohto	1	6.647-022.0	20 m		1 kpl		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	☐

■ Toimituksen mukana. ☐ Saatavilla olevat varusteet.