

# Product datasheet

Specifications



## Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m

AP8706S-WW

EAN Code: 0731304296492

## Overview

### Presentation

This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The output and input connections are C13 to C14. The cord length is 1.8m. Locking IEC system allows the use of optional locking IEC power cords for added power cord security and enhanced reliability. No tools are required to disengage the locking feature and remove the plug from the locking receptacle.

## Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C14
Cable length	1.82 mm
Number of cables	6

## Physical

Colour	Black
Height	240 mm
Width	75 mm
Depth	55 mm
Product weight	1.35 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

## Input

Max line current	10 A
Input current limits	10 A

## Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	1.8 m

## Conformance

Product certifications	CCC PSE VDE
------------------------	-------------------

## Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0...15240 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.4 cm
Package 1 Width	33.02 cm
Package 1 Length	55.8 cm
Package 1 Weight	1.21 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	26.000 cm
Package 2 Width	33.000 cm
Package 2 Length	56.000 cm
Package 2 Weight	12.950 kg

## Logistical informations

Country of origin	CN
-------------------	----

## Contractual warranty

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	179 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	170 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>
Halogen-free status	Product contains halogen above thresholds

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	30
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

