

NT 40/1 Ap L

NT 40/1 Ap L: Powerful wet and dry vacuum cleaner in the middle class with 40 litre tank. The machine impresses with excellent suction power, clever equipment and durable components.









Removable filter casing



1 Semi-automatic filter cleaning

- Semi-automatic filter cleaning guarantees constantly high suction
- The positioning of the Ap cleaning button simplifies handling.

- Permits dust-free removal of the filter.
- Effectively prevents incorrect insertion of the flat pleated filter.

Flexible hose and power cable storage

- Enables secure fixing of hoses of different lengths and diameters.
- Transport-proof storage of the power cable.

4 Clever integrated storage options for accessories

Accessories are stored safely and are always ready to hand.

TECHNICAL DATA AND EQUIPMENT





NT 40/1 Ap L

- Semi-automatic filter cleaning
- Flat pleated filter with filter casing
- Flexible hose and cable storage

Technical data		
Order no.		1.148-321.0
EAN code		4054278061351
Air flow rate	I/s	74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	1	40
Max. rated input power	W	1380
Standard nominal width		ID 35
Cable length	m	7.5
Sound pressure level	dB(A)	70
Number of motors		1
Frequency	Hz	50-60
Voltage	V	220-240
Weight	kg	12.4
Dimensions (L × W × H)	mm	525 × 370 × 630
Equipment		
Suction hose	m	2.5

Equipment		
Suction hose	m	2.5
Suction pipe	piece(s) / m	2 × 0.55 / Metal
Filter bag		fleece
Wet and dry floor nozzle	mm	300
Crevice nozzle		
Automatic switch-off at max. filling quantity		•
Flat pleated filter		Paper
Bend		
Filter cleaning		ApClean (semi-automatic filter cleaning system)
Protection class		
Steering roller stop		

■ Included in the scope of supply.

NT 40/1 AP L 1.148-321.0































		Order no.	Quantity	ID	Length	Width	Price	Description	
Suction tubes, metal									
Suction tube set, chrome-plated, NW 35 550 mm	1	2.889-191.0	1 piece(s)	ID 35	550 mm			Suction tube set, metal-chrome-plated, NW 35, 2-part, each 0.55 millimetres.	•
Flat pleated filter, paper									
Flat pleated filter, paper	2	6.904-367.0	1 piece(s)					Paper flat pleated filter (dust class M) suitable for NT 361, NT 561, NT 611 Eco/Te/M and NT 35/1, NT 45/1, NT 55/1 Eco/Eco Te/Eco M.	•
Fleece filter bags (three-ply)									
Fleece filter bags	3	2.889-154.0	5 piece(s)					Fleece filter bag with 30-litre volume. Tear-resistant, dust class M, for suction hose port in machine head.	•
Bend, plastic			1	_					
Bend Adv	_	2.889-170.0	1 piece(s)	ID 35				Ergonomic bend for the new clip system.	
DN 40 bend	5	2.889-171.0	1 piece(s)	ID 40				Bend for the new clip system in nominal size DN 40.	
Elektricky vodivé koleno, DN 40	6	2.889-172.0	1 piece(s)	ID 40				Ohyb pro nový klipový systém o velikosti DN 40. Elektricky vodivý design. Speciálně vhodný pro vysoké koncentrace jemného prachu	
Floor nozzles									
Wet/Dry floor nozzle standard	7	2.889-173.0	1 piece(s)	ID 35		300 mm		300 millimetre width, anthracite coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Incl. brush strips and squeegees.	•
Wet and dry floor nozzle Adv	8	2.889-152.0	1 piece(s)	ID 35		360 mm		360 mm wide wet and dry floor nozzle with easy-to-change inserts. Including brush strips and squeegees.	
Podlahová hubice, antracit DN40	9	2.889-174.0						Standardní podlahová hubice, antracit, s průměrem 40, s kartáčovými lištami a stěrkami. Vhodné pro všechny mokré i suché aplikace.	
Crevice nozzles		'							
Crevice nozzle NT Tact DN 35	10	2.889-159.0	1 piece(s)	ID 35	225 mm			Crevice nozzle ID 35, for new Tact range.	
Complete suction hoses (clip system	m)			'		'			
Suction hose	11	2.889-134.0	1 piece(s)	ID 35	2.5 m			2.5 m suction hose with new bayonet and clip fastener.	
	12	2.889-135.0	1 piece(s)	ID 35	4 m			4 m suction hose with new bayonet and clip fastener.	
Electrically conductive suction hose	13	2.889-136.0	1 piece(s)	ID 35	2.5 m			Electrically conductive suction hose with new bayonet and clip fastener. Length: 2.5 m.	
	14	2.889-137.0	1 piece(s)	ID 35	4 m			4 m suction hose with new bayonet and clip fastener. Electrically conductive.	
Suction hose	15	2.889-138.0	1 piece(s)	ID 40	4 m			4 m suction hose with new bayonet and clip fastener.	
	16	2.889-139.0	1 piece(s)	ID 40	2.5 m			Suction hose with new bayonet and clip fastener. Length: 2.5 m.	
Suction hose, oil-resistant	17	2.889-140.0	1 piece(s)	ID 40	4 m			Oil-resistant suction hose with new bayonet and clip fastener. Length: 4 m.	
Electrically conductive suction hose	18	2.889-141.0	1 piece(s)	ID 40	4 m			4 m, electrically conductive suction hose with new bayonet and clip fastener.	
Flat pleated filter, PES			,		,				
Flat-pleated filter packaged PES	19	6.907-662.0	1 piece(s)						
Flat pleated filter, PTFE									
Flat pleated filter, PTFE	20	6.907-455.0	1 piece(s)					Polyester fleece with PTFE coating for single-motor Tact and Ap vacuum cleaners, dust class M. Particularly suitable for very adhesive materials.	
Suction tubes, stainless steel Suction tube	21	6.902-081.0	1 piece(s)	ID 40	0.5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	
			<u> </u>					141 Vacoum cicalicis.	Щ

[■] Included in the scope of supply.

Available accessories.

NT 40/1 AP L 1.148-321.0









		Order no.	Quantity	ID	Length	Width	Price	Description
Other								
Drilling dust nozzle	22	2.679-000.0	1 piece(s)					Drilling dust nozzle for dust-free vacuuming of boreholes. Suitable for dry and wet and dry vacuum cleaners from Kärcher.
Fabric filter								
Membrane filter for the new Tact and Ap range	23	2.889-281.0						Additional membrane filter made from non-woven fabric for machines in the Tact and Ap range. To be pulled directly over the container, it enables vacuuming without a filter bag. Can be washed and reused.
Car cleaning nozzles								
Car nozzle	24	6.906-108.0	1 piece(s)	ID 35		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.
Repair kits								
Repair kit ID 35	25	2.889-149.0	1 piece(s)	ID 35				Repair kit ID 35 for the new clip system.

[■] Included in the scope of supply.

Available accessories.