


MPN: MC-USB3.0-F2B2-V2

PCIe USB3.0 3+1 Ports Expansion Card VL805

This production is a single chip USB 3.0 Host controller which enables a PCI Express equipped platform to interface with USB Super-Speed(5Gbps),High-Speed(480Mbps),Full-Speed(12Mbps), and Low-Speed (1.5Mbps) devices, Users can easy to connect your Mass Storage, Printer, Scanner , Hub, Camera and any other USB Devices to used. low profile bracket included.



- Compliant to Universal Serial Bus 3.0 Specification Revision 1.0
- Compliant to Universal Serial Bus 2.0 Specifications
- Compliant to eXtensible Host Controller Interface Specification Revision 1.0
- Compliant with PCI Express base specification 2.0
- Support Legacy USB Function, Four Down-stream ports Support Super-Speed(SS) High-Speed(HS),Full-Speed(FS) and Low-Speed(LS)
- Max. 5V/900mA power output to each USB 3.0 Port
- 4-pin power connector for extra power
- Fully plug ,play and hot plug compatible

Specifications

Design	Internal	Yes
Features	Bandwidth	5 Gbit/s
	Chipset	Via VL805
Operational conditions	Operating temperature (T-T)	5 - 35 °C
Packaging data	Quantity	1
Ports & interfaces	Host interface	PCI Express
	Output interface	USB 3.2 Gen 1 (3.1 Gen 1)
	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Power	Output current	0.9 A
	Output voltage	5 V
System requirements	Windows operating systems supported	Yes
Vendor information	Brand Name	MicroConnect
	Homepage	https://microconnect.me/
	Warranty	3 Year(s)

Other images

