TP-Link Omada EAP690E HD WLAN-tukiasema 4804 Mbit/s Valkoinen Power over Ethernet -tuki



Tuotemerkki : TP-Link **Tuoteperhe:** Omada **Tuotekoodi:** EAP690E HD

Tuotteen nimi : EAP690E HD

TP-Link Omada EAP690E HD. 2,4 GHz, 5 GHz, 6 GHz, Tiedonsiirron enimmäisnopeus: 4804 Mbit/s. Tietoturva-algoritmit: WPA, WPA2, WPA3. Ethernet LAN -datanopeudet: 10000 Mbit/s. Power over Ethernet -tuki. Tuotteen väri: Valkoinen



Ominaisuudet	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✔
Tiedonsiirron enimmäisnopeus *	4804 Mbit/s
Datan enimmäissiirtonopeus (2,4 GHz)	1148 Mbit/s
Datan enimmäissiirtonopeus (5 GHz)	2402 Mbit/s
Tiedonsiirron enimmäisnopeus (6 GHz)	4804 Mbit/s
Ethernet LAN -datanopeudet	10000 Mbit/s
Taajuuskaista	2.4 - 6 GHz
Verkkostandardit	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Automaattinen kanavanvalinta	✔
Automaattinen kanavaskannaus	✔
MIMO	✔
MIMO-tyyppi	Multi User MIMO
VLAN-tuki	✔
Nopeuden rajoitus	✔
Virranhallinnan tuki	✔
Band Steering	✔
Airtime Fairness (ATF)	✔
BeamForming-teknologia	✔

Suojaus	
Tietoturva-algoritmit *	WPA, WPA2, WPA3
Langattoman verkon tunnuksen (SSID) ominaisuudet	Multiple SSIDs
SSID-tukien lukumäärä	32
Remote Authentication Dial-In User Service (RADIUS)	✔

Liitettävyys	
Ethernet LAN (RJ-45) -portit *	1
DC-tulojakki	✔

Virranhallinta	
Power over Ethernet -tuki *	✔
Ulostulojännite	12 V

Suunnittelu	
Sijoitus *	Katto, Seinä
Tuotteen väri *	Valkoinen
Uudelleenkäynnistyspainike	✔
LED-merkkivalot	✔

Antenni	
Antennityyppi *	Sisäinen

Sertifikaatit	
Sertifiointi	CE, FCC, IC

Paino ja mitat	
Tuotteen leveys	280 mm
Tuotteen syvyys	280 mm
Tuotteen korkeus	59,1 mm

Pakkaustiedot	
Pakkauksen leveys	325 mm
Pakkauksen syvyys	393 mm
Pakkauksen korkeus	148 mm
Pakkauksen paino	3,25 kg

Pakkauksen sisältö	
Lukumäärä per pakkaus	1 kpl
Asennussarja	✔
Pika-aloitusopas	✔

Suojaus	
Pääsynhallintalista	✔

Hallintaominaisuudet	
Verkkosivupohjainen hallinta	✔
Päivitettävä Firmware	✔

Ympäristöolosuhteet	
Käytön suhteellinen kosteus (H-H)	10 - 90%
Käyttölämpötila (T-T)	0 - 40 °C
Varastointilämpötila	-40 - 70 °C
Säilytysympäristön kosteus	5 - 90%

4897098688359

4897098688366

0840030708350

840030708350

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date