TP-Link Omada EAP650-Wall 2402 Мбит/с Белый Питание по Ethernet (PoE)



Производитель : TP-Link

Семейство продуктов: Omada

Код товара: EAP650-WALL

Модель : EAP650-Wall

TP-Link Omada EAP650-Wall. 2,4 ГГц, 5 ГГц, Максимальная скорость передачи данных: 2402 Мбит/с. Алгоритмы шифрования данных: WPA, WPA2, WPA3. Скорость передачи данных Ethernet LAN: 10,100,1000 Мбит/с. Питание по Ethernet (PoE). Цвет товара: Белый



Свойства	
2,4 ГГц *	✔
5 ГГц *	✔
6 ГГц *	✘
Максимальная скорость передачи данных *	2402 Мбит/с
Максимальная скорость передачи данных (2,4 ГГц)	574 Мбит/с
Максимальная скорость передачи данных (5 ГГц)	2402 Мбит/с
Скорость передачи данных Ethernet LAN	10,100,1000 Мбит/с
Полоса частот	2.4 - 5 GHz
Стандарты сети	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3af, IEEE 802.3at
Число пользователей	100 пользов.
Автоматический выбор канала	✔
Автоматическое сканирование канала	✔
Поддержка VLAN	✔
Ограничение скорости	✔
Управление полосой пропускания	✔
Эфирная равнодоступность (ATF)	✔
Поддержка Quality of Service (QoS)	✔

Безопасность	
Алгоритмы шифрования данных *	WPA, WPA2, WPA3
Фильтрация MAC-адресов	✔
Количество поддерживаемых SSID	16
Служба удаленного подключения по телефонной линии (RADIUS)	✔

Энергопитание	
Питание по Ethernet (PoE) *	✔
Диапазон постоянного напряжения	12 V

Дизайн	
Размещение *	Стена
Цвет товара *	Белый
Кнопка сброса установок	✔
Светодиодные индикаторы	✔

Антена	
Тип антенны *	Внутренний

Сертификаты	
Сертификация	CE

Вес и размеры	
Ширина	86 mm
Глубина	86 mm
Высота	42,6 mm

Данные об упаковке	
Ширина упаковки	127 mm
Глубина упаковки	139 mm
Высота упаковки	55 mm
Масса брутто	290 g
Тип упаковки	Коробочная версия

Содержимое упаковки	
Количество в упаковке	1 шт
Краткая инструкция пользователя	✔

Условия эксплуатации	
Диапазон относительной влажности при эксплуатации	10 - 90%

Порты и интерфейсы	
Количество портов Ethernet LAN (RJ-45) *	1

Условия эксплуатации	
Диапазон температур при эксплуатации	0 - 40 °C
Диапазон температур при хранении	-40 - 70 °C
Диапазон относительной влажности при хранении	5 - 90%

4897098682104

4897098683569

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 06-NOV-2026. Prints or copies of Information are only valid on the printed Publication date