Delock Adapter Parallel DB25 male to Terminal Block 26 pin with Enclosure

Description

This terminal block adapter by Delock can be used to connect bare wires. Thus the adapter is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling.

Protection by enclosure
The plastic enclosure protects the PCB from dirt and damage.

Strain relief
The integrated strain relief fixes the cable in the enclosure.



Specification

- Connectors:
  1 x Parallel DB25 male with nuts
  1 x 26 pin terminal block
- Pin assignment: 1:1
- Pitch 1 - 16 pins: 5.00 mm
- Pitch 17 - 26 pins: 3.81 mm
- Useable for a cable gauge from 26 to 18 AWG
- Operating temperature: -20 °C ~ 105 °C
- Dimensions (LxWxH): ca. 64.8 x 56.4 x 25.0 mm

System requirements

- A free DB25 female

Package content

- Adapter
- 1 x strain relief
- 2 x locking screws

Item no. 66266

EAN: 4043619662661

Country of origin: CHINA

Package: Poly bag

Components

Images







© 2019 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

Interface	
Connector 1:	1 x Parallel DB25 male with nuts
Connector 2:	1 x 26 pin terminal block
Technical characteristics	
Operating temperature:	-20 °C ~ 105 °C
Physical characteristics	
Pitch distance:	1 - 16 pins: 5.00 mm
	17 - 26 pins: 3.81 mm
Conductor gauge:	26 - 18 AWG
Length:	64.8 mm
Width:	56.4 mm
Height:	25.0 mm

© 2019 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.