


Product Data Sheet



AromaFresh 2.0 PRO Glass

Technical Data		
Type	1030-XX	
Power rating	970-1130 [W]	
Voltage	220-240 [V]	
Frequency	50-60 [Hz]	
Weight	[kg]	
Weight with packaging	[kg]	
Height x Width x Depth	463 x 268 x 252 [mm x mm x mm]	
Height x Width x Depth packaging	505 x 338 x 278 [mm x mm x mm]	
Water tank volume	1,25 [l]	
Maximum amount of coffee	10 [cups] / [l]	
Brewing time	09:30 [mm:ss] (approx.)	
Finish brew coffee	80°C-85°C [°C] (approx.)	
Warmkeeping temperature	80°C-85°C [°C] (approx.)	
Automatic shut-off time	20-60min [min]	
Filter size	1x4	
Feature Details		Available colours:
Glass jug		1030-01 matt Black
- glass handle		1030-02 matt Black Decor
- dishwasher safe		
- removable lid		
- printed water level indication		
Water tank		
- water level indication for 2 to 10 cups		
- transparent water tank		
- removable water tank		
- removable water tank lid		
- hinged water tank lid with handle opening		
- water level visible from the front side		
Filter		
- swing filter holder with filter lock		
- removable swing filter for easy cleaning		
- removable filter		
- removable filter in black colour		
- break-proof		
- drip stop		
- dishwasher safe		
- filter size 1x4		
Housing		
- matt textured surface		
Brewing system		
- 1000W heating system		
- well-balanced brewing temperature for coffee extraction		
- two brewing modes: full power and reduced power, reduced power for 2 and 4 cup preparation		
- separate 55W heater for warm keeping		
Grinder system		
- integrated disk grinder		
- various grind settings: fine, medium, coarse		
- adjustable coffee intensity: 5 steps from mild to strong		
- grind OFF function for using pre grounded coffee		
- transparent bean container with removable lid		
- detachable upper grind head for grinder cleaning		
- cleanable ground coffee chute with enclosed cleaning brush		
Water hardness setting		
- water hardness shown on display during setting		

Calcification indication	
	- necessity to descale shown with red LED
Descaling program	
	- CALC button to start descaling program
	- remaining time shown on display
	- CALC shown on display
	- decalcification process works with reduced power for good calc removal
Brewing end signal	
	- programmable acoustic brewing end signal loudness: loud, less loud, off
	- acoustic signals for push button feedback
	- acoustic signals for brew end signal
	- all acoustic signals are able to be switched on/off
Display	
	- Multi color graphic controlled matrix display with 240 dpi
Clock	
	- display of hours and minutes
	- white illumination on black background
Timer	
	- programmable start time
	- timer clock shown on display during setting
	- white LED indication, when activated
Automatic shut-off	
	- programmable warm keeping time: 10, 20, 30, 40, 50 or 60 minutes
	- warm keeping after brewing
	- factory setting 40 minutes
	- warm keeping time shown on display during setting
	- after warmkeeping time is finished
	- manual switch-off possible
ON-OFF-Switch	
	- automatic shut-off
	- manual switch-off possible
	- ON/OFF button
	- green LED indication
Power cord	
	- cord length 80 cm
	- storage in appliance
	- power cord outlet on the back
Approvals	
	- Safety approval (GS approval mark)
	- Food law approval