

MPN: HDM191915V2.0A

HDMI 2.0 Cable, 270° angled, 1.5m

HDMI (High Definition Multimedia Interface) is one of the most used and acknowledged connections when transferring video and audio digitally from a source to a video display device or other compatible devices. This HDMI 2.0 cable is a High Performance and High Speed cable. It supports transfers up to 18 Gbps. It supports resolutions up to 4K@60Hz with HDCP 2.2, CEC, ARC and 3D. This cable is angled 270° and the design of the plug makes possible only to stick out 16mm from the wall. This is perfect when you need to install it in a flat screen, DVD player or anything like this close to the wall.



- 4K2K (60Hz), 4K2K (30Hz), 1080p (3D) (3840*2160p), including 3D video
- Gold-Plated Connectors
- Transfer rate : 18 Gbit/s
- HDCP 2.2
- Support ARC (Audio Return Channel)
- Support HDR (High Dynamic Range)
- Support CEC (Consumer Electronics Control)
- Integrated Ethernet channel which saves additional network or audio cables
- Angled plug 270°

Caractéristiques

Features	Canal de retour audio (ARC, Audio Return Channel)	Oui
	Canal Ethernet HDMI	Oui
	Compatibilité 3D	Oui
	Conformité RoHS	Oui
	Connecteur 1	HDMI Type A (Standard)
	Connecteur 2	HDMI Type A (Standard)
	Contacts du connecteur de placage	Or
	Couleur du produit	Noir
	Facteur de forme du connecteur 1	Droit
	Facteur de forme du connecteur 2	Courbe
	Genre de connecteur 1	Mâle
	Genre de connecteur 2	Mâle
	HDCP	Oui
	Longueur de câble	1,5 m
	Matière du câble	Cuivre
	Prise en charge HDR	Oui
	Quantité	1 kusû
	Résolution maximale	3840 x 2160 Pixels
	Taille des fils AWG	30
	Taux de transfert des données	18 Gbit/s
	Version HDCP	2.0
	Version HDMI	2.0

Other features	Quantité	1
Package dimensions	Depth (package,cm)	21 cm
	Gross Weight (Package, kg)	0,07 kg
	Height (package,cm)	2,4 cm
	Width (package,cm)	27,1 cm
Product dimensions	Net Weight (Product, kg)	0,05 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Année (s)
Weight & dimensions	Diamètre du câble	6 mm

Autres produits de cette série

Longueur de câble	
0,5	HDM191905V2.0A
1,0	HDM19191V2.0A
1,5	HDM191915V2.0A
2,0	HDM19192V2.0A
3,0	HDM19193V2.0A
5,0	HDM19195V2.0A