

Specifications

Eaton 3P1300UD

Eaton 3P Ellipse UPS USB DIN, 1300 VA, 840 W, Input: C14, Outputs: (4) Schuko, (4) Schuko surge only, USB charge, Tower



Photo is representative



General specifications

PRODUCT NAME	Eaton 3P Ellipse UPS
CATALOG NUMBER	3P1300UD
EAN	3553340621390
PRODUCT LENGTH/DEPTH	312 mm
PRODUCT HEIGHT	305 mm
PRODUCT WIDTH	81 mm
PRODUCT WEIGHT	7 kg
COMPLIANCES	CE Marked LVD Directive (CB) EMC Directive RoHS Directive WEEE Directive Packaging Directive Batteries Directive IEC 61643-11
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 CE UKCA Cm
MODEL CODE	Eaton 3P Ellipse 1300 USB DIN

Product specifications

SPECIAL FEATURES

- Convenient extra-flat design for easy installation in any office environment
- High performance surge-protection device compliant with IEC 61643-11 standard
- 8 outlets to connect your PC + peripherals
- 2 USB charging ports
- Card slot for optional Cloud connection
- HID-compliant USB port (cable supplied), for automatic integration with major operating systems (Windows/Mac OS/Linux)
- Easy to replace battery helps to extend UPS service life

TOPOLOGY	Offline
FORM FACTOR	Tower
CONSTRUCTION TYPE	Free standing model
COLOR	Black
VA RATING	1300VA
WATTAGE	840W
RACK MOUNTING KIT	No

PACKAGE CONTENTS

- Input cable
- USB cable
- Quick start
- Safety instructions

SURGE PROTECTION	Yes
AUTO SHUTDOWN FUNCTION	Yes
PRIMARY FREQUENCY - MAX	70 Hz
PRIMARY FREQUENCY - MIN	46 Hz
INPUT CONNECTION	C14
INPUT CORD LENGTH	1.5 m
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50-60 Hz
INPUT FREQUENCY RANGE	46-70 Hz
RECEPTACLE	(4) Schuko, (4) Schuko surge only
NUM OF OUTPUTS PC (SCHUKO)	8
VOLTAGE	230V
OUTPUT NOMINAL	230V default (220/230/240V)

Resources

VOLTAGE	
FEED TYPE	1
VOLTAGE TYPE	AC
RUNTIME GRAPH	View runtime graph
BATTERY MANAGEMENT	Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable
BATTERY RATING	12 V / 7 Ah
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	No
RUNTIME AT HALF LOAD	8.5 min
COMMUNICATION	USB port (HID compliant)
EXPANSION SLOTS	Yes
ETHERNET INTERFACE	No
INCLUDES NETWORK CARD	No
SOFTWARE COMPATIBILITY	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
USER INTERFACE	LED display
TYPE OF INTERFACE	USB
POTENTIAL FREE SWITCH CONTACT	No
ALTITUDE	3000 m
NOISE LEVEL	<25 dB at 1 meter
RELATIVE HUMIDITY	0 - 95 % (non-condensing)
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
OPERATING TEMPERATURE - MAX	40 °C
OPERATING TEMPERATURE - MIN	0 °C
OUTPUT APPARENT POWER	1300 VA
INPUT VOLTAGE - MAX	284 V
INPUT VOLTAGE - MIN	161 V
OUTPUT VOLTAGE - MAX	284 V
OUTPUT VOLTAGE - MIN	161 V
SECONDARY FREQUENCY - MAX	60 Hz
SECONDARY FREQUENCY - MIN	50 Hz
BATTERY QUANTITY	2
EFFICIENCY	97
EFFICIENCY (ECO-MODE)	97
INPUT VOLTAGE RANGE	184-264 V (adjustable to 161-284 V)
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.6
OUTPUT VOLTAGE	184-264 V (adjustable to 161-

RANGE	284 V)
PHASE (INPUT)	1
PHASE (OUTPUT)	1
RUNTIME AT FULL LOAD	1,25
COMMUNICATION INTERFACE	USB
POWER CONSUMPTION	26 W
USB INTERFACE	Yes

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. Follow us on social media to get the latest product and support information.
All other trademarks are property of their respective owners.

