



ICY BOX IB-1601MP-CU31

Mini M.2 NVMe SSD enclosure

Key features

- Fits one M.2 NVMe SSD in size 2230
- Thermal pad included for heat dissipation
- USB 3.2 Gen 2 Type-C® host connection with a transfer rate of up to 10 Gbps
- Includes lanyard for comfort and portability
- Robust, screw-fastened enclosure made of zinc alloy for optimum durability and impact resistance



Packing content

- 1x IB-1601MP-CU31
- 1x USB Type-C® to Type-C®/A cable, 30 cm
- 1x Thermal pad
- 1x Screw
- 1x Screwdriver
- 1x Lanyard
- 1x Manual



Strong and durable

Crafted from zinc alloy with a screw-fastened build, this enclosure is made of a solid level of durability in a compact format. It is designed to handle impacts, drops, and wear from daily use. It is suitable for professionals who travel frequently or do on-site work.



Easy to carry, ready to go

Here we have a practical design made for movement. Compact with a lanyard, this enclosure can travel light and stay close. Hook it to your bag, gear case, or key. Your files remain within arm's reach, ready whenever work calls.



**USB 3.2
Gen 2**

Built for speed

The USB 3.2 Gen 2 Type-C® interface delivers transfer speeds of up to 10 Gbps, making the IB-1601MP-CU31 a solid choice for high-speed workflows. Move large files or access media, it's a reliable companion for anyone working with time-sensitive content.



ICY BOX **IB-1601MP-CU31** Mini M.2 NVMe SSD enclosure

General data

Model	IB-1601MP-CU31
Article no.	61175
EAN code	4250078175094
Colour	Black
Material	Metal
Interface to host computer	USB 3.2 Gen 2 Type-C®
Length of cable	30 mm
Transfer rate	Up to 10 Gbps
UASP support	Yes
Plug & Play	Yes
LED	-
ON/OFF button	-
Chipset	-

Drive data

Drive size	22x 30 mm
Drive height	-
Drive interface	NVMe
Drive capacity	-
Supported M.2 card keys	M-Key
Space required	-
Clone function	-
HotSwap	Yes
Write protection	-

RAID data

RAID level	-
Auto rebuilding	-
Alarm	-

Additional features

Additional interfaces	-
Display	-
Control buttons	-
Lock	-
Kensington Lock	-
Degree of protection	-
Cooling	Passive
Fan volume	-

Power

Power supply	Bus powered
Plug dimension	-

Host system

Relative humidity	-
Operating temperature	-
Operating system	Windows®, macOS®, Linux®, Android™
System requirements	One free USB Type-C® or Type-A port

Logistical data

Packing unit	60 pcs. / carton
Total weight	10.60 kg
Gross weight (with packing)	0.166 kg
Net weight	0.065 kg
Dimension / carton	500x265x290 mm
Dimension (with packing)	157x130x24 mm
Dimension of article	66x45x15 mm
Country of origin	China



Best combined with



IB-DK4012-CPD

9-in-1 Mobile Docking Station with PD 100 W

[About the product](#)

IB-1612MCL-C31

Clone & Docking Station for 2x M.2 NVMe

[About the product](#)

