

MPN: BNC-HDSDI-100R

12G-SDI BNC cable 100m

MicroConnect 12G SDI cable supports signals from 12G-SDI, 6G-SDI, HD-SDI and 3G-SDI. The cable is designed for use with your professional equipment that requires an SDI connection. Support 4K60Hz for resolutions up to 4096x2160 & Full HD 1080p.
 75ohm. 12G at 75m Max.

Characteristic Impedans: 75+-3Ω

Attenuation Frequency (MHZ) - Nom. Attenuation (20C)

5 - 1.74dB/100m

50 - 4.2dB/100m

200 - 7.8dB/100m

550 - 12.85dB/100m

800 - 16.15dB/100m

1000 - 18.05dB/100m

- Designed in Denmark
- Flexible and durable: Best suited to mobile HD application
- Designed for withstanding repeated bending
- Stranded center conductor
- High-density double-braided shield.



Specifications

Features

AWG wire size	16
Cable jacket colour	Black
Cable length	100 m
Conductor material	Copper
Connector 1	Open end
Connector 2	Open end
Jacket material	Polyvinyl chloride (PVC)
Jacket outer diameter	7.3 mm
RoHS compliance	Yes

Vendor information

Brand Name	MicroConnect
Warranty	25 Year(s)

Other images

