


POWER EVOLVED



Introducing the MWE Bronze V3 230V, the evolutionary next step in Cooler Master power and the ATX 3.1 upgrade to our MWE Bronze V2 PSU. With features such as 80 Plus Bronze efficiency, a DC-to-DC + LLC circuit design, and a quiet HDB fan cooling, the V3 provides valuable performance in multiple dimensions.

Several changes and additions improve the overall user experience. Together, these design choices deliver an advanced PSU that is highly efficient and reliable. With an embossed cable, exceptional temperature resilience and a 5-year warranty, the MWE Bronze V3 will evolve your machine.

MWE BRONZE 550 V3 230V



80 Plus Bronze efficiency certification: This unit is certified to achieve more than 88% efficiency at typical loads in a 230V test.

High temperature resilience: A 40°C maximum operating temperature allows for pushing your machine to the limits with overclocking and other high-intensity applications.

Embossed cable: An embossed cable texture provides a softer and overall improved grip with a pleasing aesthetic.

ATX 3.1 support: Compliant with ATX 3.1 to fully support a peak power 1.5 times higher than the rated maximum wattage, this unit is ideal for use with the 40 series GPUs.

Single +12V rail: All power comes from a single +12V source, ensuring consistent output through all connected cables.

DC-to-DC technology: The DC-DC circuit design offers reliable, stable output to all connected components.

2 EPS Connectors: Two 4-pin EPS connectors are included for universal compatibility with currentgen motherboards.

5-year warranty: This unit comes with a standard limited manufacturing warranty of 5 years from the date of purchase.



FEATURE HIGHLIGHTS



Quiet HDB fan

A hydrodynamic bearing fan delivers long-lasting quiet and effective cooling.



80 Plus Bronze efficiency certification

Certified to achieve more than 88% efficiency at typical loads in a 230V test.



5-year warranty

This unit comes with a standard limited manufacturing warranty of 5 years from the date of purchase.



High temperature resilience

A 40°C operating temperature allows for pushing your machine to the limits.



Embossed cable

An embossed cable texture provides a softer and overall improved grip with a pleasing aesthetic.



ATX 3.1 support

After passing the ATX 3.1 peak power test, this unit is 40 series ready.

æ	n		П				м	
	P	14	П	LT.	411	H.U	IX.	۱.

Product Name		MWE Bronze 550 V3 230V		
Item Code		MPE-5501-ACABW-3B		
ATX Version		ATX 12V Ver. 3.1		
PFC		Active PFC		
Input Voltage		200 - 240V		
Input Current		5A		
Input Frequency	,	50 - 60Hz		
Dimensions (L x	W x H)	140 x 150 x 86mm		
Fan Size		120 mm		
Fan Bearing		HDB		
Efficiency		≥ 88% @ Typical Load		
80 PLUS Rating		80 PLUS Bronze		
ErP 2014 Lot 3		Yes		
Operating Temp	perature	0 ~ 40°C		
Power Good Sig	nal	100 - 150ms		
Hold Up Time		≥ 16ms		
MTBF		>100,000 hours @ 25°C ambient		
Protections		UVP / OVP / OPP / OTP / SCP		
Regulatory		TUV, CE, FCC, CCC, EAC, RCM, UKCA, RoHS2.0 / BIS, KC (based on region's request.)		
Connectors	ATX 24 Pin	x1 = 1x (500mm)		
	EPS 8Pin / 4+4 Pin	x2 = 1x (550+120mm)		
	SATA	x6 = 2x (400+150+150mm)		
	Peripheral 4 Pin	x3 = 1x (400+150+150mm)		
	PCI-e 6+2 Pin	x2 = 1x (500+120mm)		

AC INPUT		20	00-240V~ 5A 50 - 60	Hz	
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	17A	17A	45A	0.3A	3A
TOTAL POWER	110W		540W	3.6W	15W
			550W		

PACKING INFORMATION Cable Type **EAN** UPC MPE-5501-ACABW-3BUK 4719512145098 884102117411 MPE-5501-ACABW-3BEU 4719512145104 884102117428 MPE-5501-ACABW-3BST 4719512145111 884102117435 MPE-5501-ACABW-3BAU 4719512145128 884102117442 MPE-5501-ACABW-3BBR 4719512145135 884102117459

4719512150627

4719512145159

4719512145166

884102122941

884102117473

884102117480

MPE-5503-ACABW-3BKR

MPE-5501-ACABW-3BIN

MPE-5501-ACABW-3BTH

Net Weight	1.45 kg / 3.196 lb
Gross Weight	1.85 kg / 4.080 lb
Package Dimensions	245 x 190 x 110mm (9.65 x 7.48 x 4.33")
Carton Dimensions	570 x 260 x 215mm (22.44 x 10.24 x 8.46")
Unit / Carton	5 pcs
Carton / Pallet	32 pcs

- All images and descriptions are solely for example purposes.
- Specifications, features, and prices are subject to change without notice.
- Specifications, appearances, and features may vary by model and region. Please refer to official specification pages for full details.
- Unless otherwise stated, all performance claims are based on theoretical performance. Actual figures may vary in real-world situations.
- Any configuration other than original product configuration is not performance guaranteed.