EPSON

Epson TM-U295 (272): Serial, w/o PS, ECW



Brand : Epson

Product code: C31C163272

Product name : Epson TM-U295 (272): Serial, w/o PS, ECW

TM-U295 Slip Printer/ White/ RS-232C

Epson TM-U295 (272): Serial, w/o PS, ECW:

Authorisation slip printer



SLIP IMPACT PACKAGED PRINTER; Serial; Epson Cool White (ECW); no Power Supply
Epson TM-U295 (272): Serial, w/o PS, ECW. Character density: 16.2 cpi. Printing media thickness: 0.09/0.35 µm. Connectivity technology: Wired, Interface: RS-232, Drawer kick-out. Sound pressure level (printing): 65 dB, Mean time between failures (MTBF): 180000 h, Country of origin: Japan. Product colour: White

Printing	
Colour	✕
Character density	16.2 cpi
Paper handling	
Printing media thickness	0.09/0.35 µm
Ports & interfaces	
Connectivity technology *	Wired
Interface	RS-232, Drawer kick-out
Features	
Sound pressure level (printing)	65 dB
Mean time between failures (MTBF)	180000 h
Country of origin	Japan
Maximum number of copies	2 copies
Ribbon life	1.5 million characters
Safety	UL, CSA C22.2 No. 950
Design	
Product colour *	White
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	30 - 85%
Storage relative humidity (H-H)	30 - 90%
Weight & dimensions	
Width	180 mm
Depth	191 mm
Height	102 mm

Weight & dimensions	
Weight	1.6 kg
Packaging data	
Quantity per pack	1 pc(s)
Package width	235 mm
Package depth	270 mm
Package height	185 mm
Package weight	1.84 kg
Logistics data	
Harmonized System (HS) code	84433210
Products per master (outer) case	4 pc(s)
Master (outer) case width	300 mm
Master (outer) case length	485 mm
Master (outer) case height	405 mm
Products per pallet	120 pc(s)
Products per pallet layer	24 pc(s)
Pallet gross width	120 cm
Pallet gross height	100 cm
Products per pallet (UK)	160 pc(s)
Products per pallet layer (UK)	32 pc(s)
Pallet length (UK)	120 cm
Pallet height (UK)	137 cm
Technical details	
Box contents	Main unit, Ribbon, User manual
Other features	
Dimensions (WxDxH)	180 x 190.5 x 101.5 mm
Electromagnetic compatibility	VCCI class A, FCC class A, CE marking

8715946319667

3540260032221

5711045342707

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 18-NOV-2026. Prints or copies of Information are only valid on the printed Publication date