# Epson EB-L520U

**Brand :** Epson

**Product code:** V11HA30040

**Product name :** EB-L520U





- High brightness, scalable size: Provides 5,200 lumens high-brightness display at up to 500"
- Premium display features: Full HD, supports 4K input, edge-blending and geometric correction
- Unrestricted viewing: Free from pixilation, glare, fingerprints and a central bevel
- Social distancing support: Scalable display meets the needs of every audience configuration
- Plug, click and collaborate: Collaborate using Epson’s wireless presentation system - ELPWP10

EB-L520U
Epson EB-L520U. Projector brightness: 5200 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Video processing: 10 bit, Colour modes (2D): Cinema, Dynamic, sRGB, DICOM SIM, Presentation, Video colour modes: Cinema, DICOM simulation mode, Dynamic, Presentation, sRGB. Serial interface type: RS-232C

| Projector | |
|---|---|
| Screen size compatibility * | 1270 - 12700 mm (50 - 500") |
| Contrast ratio (dynamic) | 5000000:1 |
| Projector brightness * | 5200 ANSI lumens |
| Projection technology * | 3LCD |
| Projector native resolution * | WUXGA (1920x1200) |
| Contrast ratio (typical) * | 2500000:1 |
| Native aspect ratio * | 16:10 |
| Number of colours | 1.07 billion colours |
| Projector brightness (economic mode) | 3640 ANSI lumens |
| Vertical scan range | 192 - 240 Hz |
| Keystone correction, horizontal | ±30° |
| Keystone correction, vertical | ±30° |
| Matrix size | 1.7 cm (0.67") |

| Light source | |
|---|---|
| Light source type * | Laser |
| Service life of light source * | 20000 h |
| Service life of light source (economic mode) | 30000 h |

| Lens system | |
|---|---|
| Focus * | Manual |
| Focal length range | 20 - 31.8 mm |
| Aperture range (F-F) | 1.5 - 1.7 |
| Zoom capability | ✔ |
| Zoom type | Manual |
| Zoom ratio | 1.6:1 |
| Throw ratio | 1.35 - 2.20:1 |

| Video | |
|---|---|
| Analog signal format system * | Not supported |
| Full HD * | ✔ |
| 3D * | ✘ |
| Video processing | 10 bit |
| Colour modes (2D) | Cinema, Dynamic, sRGB, DICOM SIM, Presentation |
| Video colour modes | Cinema, DICOM simulation mode, Dynamic, Presentation, sRGB |

| Design | |
|---|---|
| Product colour * | White |
| Placement | Ceiling, Desktop, Floor, Wall |
| Cable lock slot | ✔ |
| Cable lock slot type | Kensington |

| Display | |
|---|---|
| Built-in display * | ✘ |

| Power | |
|---|---|
| Power source * | AC |
| Power consumption (typical) * | 293 W |
| Power consumption (standby) * | 0.3 W |
| Power consumption (economy mode) | 223 W |
| AC input voltage | 100 - 240 V |
| AC input frequency | 50 - 60 Hz |

| Software | |
|---|---|
| Software support | via: AMX, Crestron (Network), Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol |

| Operational conditions | |
|---|---|
| Storage temperature (T-T) | -10 - 60 °C |
| Operating relative humidity (H-H) | 20 - 80% |
| Storage relative humidity (H-H) | 10 - 90% |

| Weight & dimensions | |
|---|---|
| Width | 440 mm |
| Depth | 304 mm |
| Height | 122 mm |
| Weight * | 7.7 kg |
| Package width | 495 mm |
| Package depth | 530 mm |
| Package height | 210 mm |
| Package weight | 10.4 kg |

| Packaging content | |
|---|---|
| Remote control included * | ✔ |
| Batteries included | ✔ |

| Ports & interfaces | |
|---|---|
| USB 2.0 ports quantity | 2 |
| USB 2.0 Type-B ports quantity | 1 |
| Audio (L/R) in * | 1 |
| Serial interface type * | RS-232C |
| VGA (D-Sub) ports quantity * | 3 |
| HDMI ports quantity * | 2 |
| DVI port * | ✗ |

| Network | |
|---|---|
| Ethernet LAN * | ✔ |
| Wi-Fi * | ✔ |
| Wi-Fi standards | 802.11a, Wi-Fi 4 (802.11n) |

| Storage | |
|---|---|
| Card reader integrated * | ✗ |

| Features | |
|---|---|
| Noise level (economic mode) | 23 dB |
| Noise level * | 31 dB |
| Country of origin | Philippines |

| Multimedia | |
|---|---|
| Built-in speaker(s) * | ✔ |
| RMS rated power | 10 W |
| Number of built-in speakers | 1 |

| Design | |
|---|---|
| Market positioning * | Presentation |
| Product type * | Standard throw projector |

| Packaging content | |
|---|---|
| Cables included | AC, HDMI |
| Warranty card | ✔ |
| Bundled software | EasyMP Multi PC Projection |

| Technical details | |
|---|---|
| Other features | 21:9 aspect ratio support, A/V mute, Arc Correction, Built-in speaker, CEC compatible, Easy OSD pre-setting, Edge Blending, Long light source life, PC Free, Quick Corner, Screen share, Source function, Ultra-wide display (16:6), iProjection App |
| USB display function | 3 in 1: Image / Mouse / Sound |
| Sustainability certificates | TCO |
| Mobile app support | ✔ |
| Power consumption | 234 Watt (Normal On-Mode), 164 Watt (Eco On-Mode), 293 Watt (Normal Peak-mode), 223 Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby) |

| Logistics data | |
|---|---|
| Quantity per pack | 1 pc(s) |
| Products per pallet | 14 pc(s) |
| Pallet gross weight | 0 g |
| Products per pallet (UK) | 14 pc(s) |
| Pallet weight (UK) | 0 g |
| Harmonized System (HS) code | 85286200 |

| Other features | |
|---|---|
| Option type | Air filter, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP10, Wireless LAN unit, Wireless transmitter - ELPWT01 |
| Interface | RS-232C, VGA in (2x), VGA out, HDMI in (2x), HDBaseT, Miracast (optional), Jack plug out, Jack plug in (2x), USB 2.0-A, USB 2.0, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac (optional) |
| Control panel | 0.67 inch with C2 Fine |
| Box contents | HDMI Cable, Main unit, Power cable, Remote control incl. batteries, User guide, Warranty Documents |
| Security features | Kensington lock, Padlock, Security cable hole, Wireless LAN unit lock |

8715946695563

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 17-NOV-2026. Prints or copies of Information are only valid on the printed Publication date